SAXON

Registered Trade Mark

heavy duty range

scissor lift platforms

design
manufacture
install
commission

Strength in Design

SAXON HEAVY DUTY RANGE OF SCISSOR LIFT PLATFORMS

SINGLE SCISSOR LIFT PLATFORM RANGE

Type X	Load Kg	Length min L	Width min W	Closed Height C	Travel T	Speed mm/sec	Motor Kw
SL 2.0-800-.75	2000	1350	750	260	800	30	1.1
SL 2.0-800-1.0	2000	1350	1000	260	800	30	1.1
SL 2.0-1200-.75	2000	1850	750	260	1200	30	1.1
SL 2.0-1200-1.0	2000	1850	1000	260	1200	30	1.1
SL 2.0-1500-1.0	2000	2200	1000	285	1500	55	2.2
SL 2.0-1500-1.5	2000	2200	1500	285	1500	55	2.2
SL 2.0-2000-1.5	2000	3000	1500	360	2000	45	2.2
SL 2.0-2000-2.0	2000	3000	2000	360	2000	45	2.2
SL 3.0-1200-1.0	3000	1850	1000	285	1200	40	2.2
SL 3.0-1200-1.5	3000	1850	1500	285	1200	40	2.2
SL 3.0-1500-1.0	3000	2200	1000	325	1500	40	2.2
SL 3.0-1500-1.5	3000	2200	1500	325	1500	40	2.2
SL 4.0-800-1.0	4000	1400	1000	360	800	35	2.2
SL 4.0-800-1.5	4000	1400	1500	360	800	35	2.2
SL 4.0-1300-1.0	4000	2100	1000	360	1300	40	3.0
SL 4.0-1300-1.5	4000	2100	1500	360	1300	40	3.0
SL 4.0-1600-1.5	4000	2500	1500	360	1600	40	3.0
SL 4.0-1600-2.0	4000	2500	2000	360	1600	40	3.0
SL 4.0-2000-1.5	4000	3000	1500	460	2000	35	4.0
SL 4.0-2000-2.0	4000	3000	2000	460	2000	35	4.0
SL 6.0-1300-1.0	6000	2100	1000	410	1300	25	3.0
SL 6.0-1300-1.5	6000	2100	1500	410	1300	25	3.0
SL 6.0-1600-1.5	6000	2600	1500	410	1600	45	4.0
SL 6.0-1600-2.0	6000	2600	2000	410	1600	45	4.0
SL 6.0-2000-1.5	6000	3000	1500	500	2000	30	4.0
SL 6.0-2000-2.0	6000	3000	2000	500	2000	30	4.0
SL 10.0-1000-1.5	10000	1850	1500	575	1000	15	4.0
SL 10.0-1000-2.0	10000	1850	2000	575	1000	15	4.0
SL 10.0-1500-1.5	10000	2600	1500	575	1500	15	4.0
SL 10.0-1500-2.0	10000	2600	2000	575	1500	15	4.0
SL 10.0-2000-1.5	10000	3200	1500	675	2000	20	5.5
SL 10.0-2000-2.0	10000	3200	2000	675	2000	20	5.5
SL 15.0-1000-1.5	15000	1850	1500	725	1000	15	4.0
SL 15.0-1500-2.0	15000	2700	2000	775	1500	15	4.0
SL 15.0-2000-2.0	15000	3400	2000	825	2000	15	4.0
SL 20.0-1000-1.5	20000	2100	1500	825	1000	10	4.0
SL 20.0-1500-2.0	20000	2800	2000	875	1500	10	4.0

TANDEM SCISSOR LIFT PLATFORM RANGE

Type XX	Load Kg	Length min L	Width min W	Closed Height C	Travel T	Speed mm/sec	Motor Kw
TL 4.0-800-.75	4000	2700	750	300	800	30	2.2
TL 4.0-800-1.0	4000	2700	1000	300	800	30	2.2
TL 4.0-1200-.75	4000	3700	750	300	1200	30	2.2
TL 4.0-1200-1.0	4000	3700	1000	300	1200	30	2.2
TL 4.0-1500-1.0	4000	4400	1000	310	1500	50	4.0
TL 4.0-1500-1.5	4000	4400	1500	310	1500	50	4.0
TL 4.0-2000-1.5	4000	6000	1500	410	2000	40	4.0
TL 4.0-2000-2.0	4000	6000	2000	410	2000	40	4.0
TL 6.0-1200-1.0	6000	3700	1000	310	1200	35	4.0
TL 6.0-1200-1.5	6000	3700	1500	310	1200	35	4.0
TL 6.0-1500-1.0	6000	4400	1000	360	1500	35	4.0
TL 6.0-1500-1.5	6000	4400	1500	360	1500	35	4.0
TL 8.0-800-1.0	8000	2800	1000	410	800	30	4.0
TL 8.0-800-1.5	8000	2800	1500	410	800	30	4.0
TL 8.0-1300-1.0	8000	4200	1000	410	1300	35	5.5
TL 8.0-1300-1.5	8000	4200	1500	410	1300	35	5.5
TL 8.0-1600-1.5	8000	5000	1500	410	1600	35	5.5
TL 8.0-1600-2.0	8000	5000	2000	410	1600	35	5.5
TL 8.0-2000-1.5	8000	6000	1500	510	2000	25	5.5
TL 8.0-2000-2.0	8000	6000	2000	510	2000	25	5.5
TL 12.0-1300-1.0	12000	4200	1000	470	1300	20	5.5
TL 12.0-1300-1.5	12000	4200	1500	470	1300	20	5.5
TL 12.0-1600-1.5	12000	5200	1500	470	1600	30	5.5
TL 12.0-1600-2.0	12000	5200	2000	470	1600	30	5.5
TL 12.0-2000-1.5	12000	6000	1500	540	2000	25	5.5
TL 12.0-2000-2.0	12000	6000	2000	540	2000	25	5.5
TL 20.0-1000-1.5	20000	3700	1500	625	1000	10	5.5
TL 20.0-1000-2.0	20000	3700	2000	625	1000	10	5.5
TL 20.0-1500-1.5	20000	5200	1500	625	1500	10	5.5
TL 20.0-1500-2.0	20000	5200	2000	625	1500	10	5.5
TL 20.0-2000-1.5	20000	6400	1500	725	2000	10	5.5
TL 20.0-2000-2.0	20000	6400	2000	725	2000	10	5.5
TL 30.0-1000-1.5	30000	3700	1500	800	1000	8	5.5
TL 30.0-1500-2.0	30000	5400	2000	850	1500	8	5.5
TL 30.0-2000-2.0	30000	6800	2000	900	2000	8	5.5
TL 40.0-1000-1.5	40000	4200	1500	900	1000	5	5.5
TL 40.0-1500-2.0	40000	5600	2000	925	1500	5	5.5

LORRY LOADER SCISSOR LIFT PLATFORM RANGE

Type X	Load Kg	Length L	Width W	Closed Height C	Travel T	Speed mm/sec	Motor Kw
LL 4.0-1600-2.0	3000	3000	2500	360	1600	50	4.0
LL 4.0-2000-2.0	3000	4000	2500	460	2000	60	5.5
LL 6.0-2000-2.0	5000	4200	2500	460	2000	50	5.5
LL 6.0-3000-2.0	5000	5000	2500	600	3000	35	7.5
LL 15.0-2000-2.0	10000	5000	2500	825	2000	50	11.0

For Tandem Lifts Closed Height + 50mm and Double Length and Motor Rating

DOUBLE VERTICAL SCISSOR LIFT PLATFORM RANGE

Type X	Load Kg	Length min L	Width min W	Closed Height C	Travel T	Speed mm/sec	Motor Kw
DV 2.0-1500-1.0	2000	1350	1000	400	1500	30	1.1
DV 2.0-1500-1.5	2000	1350	1500	400	1500	30	1.1
DV 2.0-2000-1.0	2000	1700	1000	500	2000	60	2.2
DV 2.0-2000-1.5	2000	1700	1500	500	2000	60	2.2
DV 3.0-3200-1.0	3000	2500	1000	650	3200	55	4.0
DV 3.0-3200-1.5	3000	2500	1500	650	3200	55	4.0